

## RCI PSM-2P-H

# 125kHz standard security ISO imagable credential



#### RCI PSM-2P-H 125kHz ISO imageable credential

RCI Pyramid sets the electronic security benchmark for 125-kHz proximity readers, cards, and tags. Based upon proven contactless digital radio frequency identification (RFID) technology, Pyramid readers interface with a wide range of electronic access control systems by complying with either the legacy Wiegand or the latest bi-directional Open Supervised Device Protocol (OSDP). They offer

value-add features such as MAXSecure™ and fleaPower™, and can be ordered to support several proximity card and tag technologies. Additionally, Pyramid cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered to support several proximity reader technologies.



### Specifications - PSM-2P-H

**Technology** Proximity

Frequency Excitation (125 kHz)

Operation Passive (no battery)

Type ISO

Formats Wiegand (26-bit)

Material PVC

Color Glossy white

**Slot punch** Vertical and horizontal indicators

Marking Date code and ID

Imaging Supports dye sublimation imaging

**Read range** Up to 7 inches (176 mm)

Warranty 12 months

**Dimensions** 2.1" W × 3.4" H × 0.031" D (53 mm × 86 mm × 0.79 mm)

**Weight** 0.19 oz (5.5 g)

Operating temperature  $-35^{\circ}$  F to 122° F ( $-37^{\circ}$  C to +50° C)

**Humidity** 0–95% non-condensing

Technologies supported RCI Pyramid; certain HID 125-kHz Proximity protocols supported; certain AWID 125-kHz

Proximity protocols supported

#### NOTES:

Matching internal and external sequential coding standard. If printing, please verify that the printer (or overlay) supports credential type/thickness. Installation scenario may affect read range. Supporting readers include, but are not limited to, P-300-H, P-500-H, P-640-H, P-710-H, P-900-H, PCR35L, PCR620L, PCR640L as well as HID products including ProxPoint® Plus, ThinLine II®, MiniProx®, and MaxiProx.

© dormakaba 2024 Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation.

Any questions? We would be happy to advise you.

Contact us at: 1-800-265-6630