

E-Plex[®] Electronic Standalone Locks

5070/5270/5770 Series



Applications

Helping protect people and everything that matters. E-Plex 5x70 Series makes upgrading locking systems easy.


The electronic PIN/Card solution is ideal for dual-swing doors, parking gates, and glass doors. Featuring online-type functionality in a stand-alone model, E-Plex 5x70 series models are easy-to-install. The reader housings with keypad eliminates problems and costs associated with issuing, controlling, and collecting keys.

The E-Plex 5x70 provides exterior access control for multiple users using specific PINs (Personal Identification Numbers)—E-Plex 5070 and 5270 and/or Cards (PROX—E-Plex 5770).


E-Plex 5x70 series benefits

- Up to 3000 users
- PIN code length adjustable up to 8 digits
- Programming: E-Plex 5070 at the lock; E-Plex 5270 via required E-Plex Enterprise or Aurora Software (not included); E-Plex 5770 via optional E-Plex Enterprise or Aurora software (not included).
- Scheduling: Up to 16 different access schedules may be programmed.
- Holiday/Vacation Up to 32 different holiday/vacation blocks may be programmed.
- Operating modes: Access (via Credential); Lockout; Passage (toggled on/off or preprogrammed); Scheduled Access (5270 and 5770 only)
- Anti-tamper lockout is adjustable from 3 to 9 invalid attempts with an adjustable period of 0 to 20 seconds
- 5 authority access levels let you determine who has privileges to specific lock functions (Six authority levels 5270 and 5770 models)
- Minimum of 9000 stored audit events (with optional software). Maximum 30,000 events (software required)
- Vandal Resistance: Exclusive tamper-switch circuitry in reader housing prevents unauthorized access if unit is

attacked or removed from mounting plate. If tamper is detected, the reader unit emits constant bright blue lights and all internal wire other than power become passive until unit is reset.



E-Plex 5070/5270



E-Plex 5770

E-Plex Specifications

Finish options	Standard: Satin Chrome (626); Black (676) Optional: Bright Brass (605); Satin Brass (606); Bright Chrome (625); Dark Bronze (simulates 10B-613)
Code Length	4 to 8 Digits
Code Capacity	Up to 3000 (dependant on model)
Event Audit Trail	9000 - E-Plex 5070; 30,000 - E-Plex 5270 and 5770 (with software)
Environmental	Indoor/Outdoor
Operating Temperature	Front Housing: -31 °F (-35 °C) to + 151 °F (66 °C)
Construction	Solid cast housings
Items Supplied	Installation manual, quick reference guide, operations manual, full-scale template, and required installation hardware
Lock Features	Audit Trail, Passage Mode
Accessibility	Americans with Disabilities Act (ADA)
Access Type	Keypad (PIN)
Fire Rating	3-hour UL/ULC fire rating for A labeled doors
Weight	5.26 lbs. (2.38 kg)
Power requirements	12–24 VDC regulated power input from standard, off-the-shelf regulated power supplies. If power is lost, user data and lock parameters are retained in on-board memory. Power supply must have battery backup (battery located in interior housing cover)
Warranty	3 Year Manufacturer

© dormakaba 2023 Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation.

Any questions? We would be happy to advise you.