

dormakaba Gateway GEN II



Features

- End-to-End Encryption
- Radio Frequency (RF) communications at 2.4 GHz, which is globally license-free
- Secure networking (128 AES encryption)
- Self-forming networks
- ZigBee Prostack standard (large scale, network stability, resilient):
 - Ideal for large scale properties (thousands of nodes)
 - Asymmetric link handling
 - Network stability even when nodes are within close proximity
 - Extended battery life with deep and special parent functions
 - Resilient – ensured by frequency agility

dormakaba Gateway GEN II

Elevating hotel's security infrastructure with the dormakaba Gateway GEN II, an online device seamlessly connecting standalone electronic door locks and the access control system through the ZigBee communications protocol. Purpose-built for dormakaba Zigbee enabled locks, this gateway reinvents how you manage and monitor access in your hospitality establishment.

The GEN II Gateway serves as the vital link between your hotel's access control system and the Zigbee-enabled locks, ensuring a robust and responsive connection. Enjoy the

benefits of wireless communication and data transfer, allowing you to effortlessly oversee and control door access remotely. Designed for hotels, our gateway facilitates a dynamic interplay between the front desk and electronic locks, optimizing work processes and enhancing the overall guest experience.

Our Gateway GEN II enables seamless, secure, and efficient wireless connectivity in the realm of hotel access control.

Applications

The dormakaba Gateway GEN II online system is ideal for hotels seeking the ultimate in security and guest experience while maximizing operational efficiency.

This wireless online system offers a two-way communication between the front desk and the hotel's electronic locks, allowing to monitor and manage room door activity.

Physical Characteristics

Standards / Protocols	2.4 GHz DSS, IEEE 802.15.4, ZigBee compliant platform, DHCP, DNS Discovery
I/O Port	1 x 100 Mbit PoE capable Ethernet
Cabling Type	Ethernet – RJ45 Cat 5 or better
Dimensions	3.6W x 1.025H x 5.37L inches (91.44W x 26.03H x 136.4L mm)
RF Data Rate	3 Mbps
RF Sensitivity	Better than -97dBm
Transmit Power	<ul style="list-style-type: none">• 10 mW for 74562 (Europe/Asia)• 158 mW for 74563 (North America)• 87 mW for 74564 (International)
Power Input	5VDC +/- 0.25V for USB and 37 to 57VDC for PoE
Environmental Conditions	<ul style="list-style-type: none">• Operating Temperature: 0 to 50 °C (32 to 122 °F)• Humidity: 0 to 95% RH, non-condensing• Indoor Range: 30-55 meters (74563); 25-40 meters (74564); 20-30 meters (74562)

Certifications

Standards	<ul style="list-style-type: none">• RoHS Compliant• Power Over Ethernet (PoE) Power Sources for Access Control Systems and Equipment [UL294B:2013 Ed.1+R:02Feb2015]• Alarm and Electronic Security Systems - Part 11-1: Electronic Access Control Systems - System and Components Requirements [CAN/ULC 60839-11-1:2016 Ed.1]• Audio/Video, Information and Communication Technology Equipment – Part 1: Safety Requirements (R2019) [CSA C22.2#62368-1:2014 Ed.2]• Complies with FCC part 15C class A and RSS210• Complies with CE Radio Equipment Directive 2014/53/EU
-----------	---



© dormakaba 2024. Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation.

Any questions? We would be happy to advise you.

Contact us at: +800.999.6213