



1. The ICU1200 Pair door package consists of:
 - A. RTS88 series size 3 overhead concealed double acting manual swing door closer with 90° hold open.
 - B. Panels:
 - 2-5/8" [67] Narrow stile door panels (including 3/4" [19] wide glass stop).
 - 3-1/4" [83] Optional muntin mounted at 41-3/4" [1060] centerline on all panels (including 3/4" [19] wide glass stop).
 - 4" [102] Bottom rails (including 3/4" [19] wide glass stop).
 - 1-3/4" [44] x 4-1/2" [114] Smooth jambs.
 - Vertical and horizontal brush type weather stripping.
 - 3/4" [19] wide snap-in glass stops for glazing from 1/4" [6] to 1-1/4" [32] at 1/8" [3] increments.
 - Dorma heavy duty bottom pivot.
 - Bottom Door Sweep.
 - Pull Handles
 - 1/4-20 Rivet nut installation tool required for handles on bi-fold door panels (Ex: 95585A600 McMaster-Carr or equivalent)
 - C. Finishes:
 - Clear anodized (BHMA 204).
 - Dark Bronze anodized (BHMA 313).
2. Typical Package Options:
 - A. Finishes: special anodized, PVDF (wet) paint, powder coat, and cladding available. header, panels and jambs only.
 - B. Muntins: multiple, various heights, locations and crashbars available.
 - C. Bottom Rails: 7" [178], 10" [254]. Other options available.
 - D. Santoprene rubber weather stripping available.
 - E. Jambs: single offset pocket 1 3/4" [44] x 4 1/2" [114] and 2" [50] x 6" [152] smooth available.
 - F. Optional ADA Compliant Surface applied track and threshold 1/2" [13] x 4 1/2" [114].
 - Various thresholds available.
 - G. Push/Pull bars
 - H. Manual two point mortise lock with thumb turn and key cylinder.
3. Drawing Notes:
 - A. Drawing dimensions are in English & Metric units. Metric units are displayed as: 1" [25] millimeters.
 - B. Typical package dimensions: (Glass thickness may be limited by panel size)
 - Each door package is manufactured to your custom size requirements.
 - Package Width: Min. 7'-0" [2134] to Max. 9'-11 1/4" [3029].
 - Package Height: Min. 6'-10 3/4" [2197] to Max. 9' [2743]
 - Bi-Fold Panel Width: Max. 36" [914].
 - Bi-Fold Panel Weight: Max. 150 lbs. [68kg].
 - Door Panel Width: Max. 42" [1067].
 - Door Panel Weight: Max. 320 lbs. [145kg].
 - C. Maximum Opening Angle 90°.
4. Standards of Compliance:
 - A. Designed to comply with these standards depending on installation and application:
 - International Building Code (Section 1008).
 - NFPA 101 Life Safety Code (Section 7.2.1.9).
 - B. Refer to Local, State, National or AHJ. Building Code for minimum door height and minimum/maximum width allowable for egress requirements.
 - C. Minimum ADA is 32" clear slide /swing opening.
5. Contact Dorma Architectural Services for more information:
 - A. Email: SPECNOW@dorma.com
 - B. Phone: 1-844-SPEC-NOW (1-844-773-2669)


SHIPPED AS UNIVERSAL ASSEMBLY: ALL HANDING PERMUTATIONS ARE SHOWN BELOW AND WILL BE CONFIGURED AT INSTALLATION.




APPLICATION TYPE
LEFT HAND OUT-SWING BI-FOLD PANELS
WITH DOUBLE ACTING SWING DOOR
(SHOWN IN DRAWING)



APPLICATION TYPE
RIGHT HAND OUT-SWING BI-FOLD PANELS
WITH DOUBLE ACTING SWING DOOR



APPLICATION TYPE
RIGHT HAND IN-SWING BI-FOLD PANELS
WITH DOUBLE ACTING SWING DOOR



APPLICATION TYPE
LEFT HAND IN-SWING BI-FOLD PANELS
WITH DOUBLE ACTING SWING DOOR

ICU1200

Sheet 1 of 1

DORMA USA Inc.
924 Sherwood Dr. Lake Bluff, IL 60044 Phone: 800-523-8483



Drawing Title: **ICU1200 MANUAL BI-FOLD/SWING DOOR PACKAGE**
DOUBLE ACTING NARROW STILE

© DORMA USA Inc. Subject to Change Without Notice. Date: 24-SEP-2015