

# E-Plex® 7900

## Integrated RFID Electronic Lock



### Features and benefits:

- Functions in wireless mode with Keyscan Aurora V 1.0.15.0 (later)
- Functions in offline mode with Keyscan LUNA V2.0 or Aurora V1.0.22.0 (or later)
- Can be utilized in conjunction with E-Plex 3x00 Series and E-Plex 5x00 series electronic wireless locks
- Compatible with most credential technologies, including Keyscan BLE mobile credentials
- Less projection from door
- Integrated RFID reader
- Integrated wireless antenna
- Batteries and wireless antenna on the secure side of the door
- Offers door monitoring capabilities
- Top mounted LED indicators

### Next generation E-Plex electronic wireless locks

With a streamlined design, this heavy duty electronic lockset is built for performance. The most versatile E-Plex model to date, it functions in standalone or wireless modes for cylindrical, mortise and exit device applications. The E-Plex 7900 when used with Keyscan Aurora or LUNA software, offers the same trusted function and reliability customers have come to love with other E-Plex product offerings.

With variable models each designed to function with a designated list of credential types, E-Plex 7900 can be trusted in many access control environments.

### A cost effective wireless lock solution

The E-Plex 7900 wireless model integrates with Keyscan Aurora software using a ZigBee wireless network, which creates a two-way communication from lock to Aurora software. This allows installation of up to 25 locks per gateway and 2 router hops to a maximum of 100 E-Plex 7900 wireless locks per gateway on any system running Keyscan Aurora version 1.0.15 or later. E-Plex 7900 also function on networks utilizing other E-Plex wireless lock models using the same credentials.



Each lock can be offline programmed with the same data from Keyscan Aurora OR LUNA software. The data is then uploaded

to each lock using a handheld M-Unit. (NOTE: this requires LUNA 2.0 or Aurora version 1.0.22 or later).

E-Plex 7900 locks will each function with a specified series of either high frequency (13.56 MHz) or standard frequency (125 kHz) credential types.

## Factsheet

## Typical E-Plex 7900 offline or wireless application



### Offline / Standalone

- Program each lock directly
- Data and permissions are transferred from Keyscan Aurora or LUNA software and uploaded to each lock using M-Unit handheld

### Integrated Wireless Network

- Up to 100 gateways per network
- Up to 100 devices (locks/ routers) per gateway
- Up to 8 routers per gateway
- Locks can be up to 2-hops from gateway

### Specifications

<b>Description</b>	Heavy duty, electronic lockset with clutch mechanism and built-in contactless RFID reader.
<b>Handing</b>	Cylindrical lock is dual handed. Field reversible levers.
<b>Key Override</b>	Ilco KIL cylinder, keyed different. Best (SFIC) and equivalents (core not included).
<b>Latch</b>	1/2" (13 mm) Deadlatch
<b>Door Thickness</b>	From 1 3/8" to 2 1/2" (35mm to 66mm).
<b>iCLASS legacy (Public Key)</b>	HID 13.56 MHz iClass Classic; HID Corporate 1000 (35, 48 bit); Keyscan 36-bit; Open format 26-bit; HID 37-bit (H10304); MiFare Classic (CSN Only)
<b>iCLASS SEOS (Public Key)</b>	HID 13.56 MHz iClass SEOS; HID Corporate 1000 (35, 48 bit); Keyscan 36-bit; Open format 26-bit; HID 37-bit (H10304)
<b>iCLASS SE &amp; Legacy (Keyscan Elite Key)</b>	HID 13.56 MHz iClass Legacy; SR and SE with Keyscan Elite Key; Keyscan 36-bit
<b>Standard Proximity (125 kHz)</b>	Keyscan 36-bit format; HID Corporate 1000 (35, 48-bit); HID 26 bit
<b>Mifare with BLE (13.56 MHz)</b>	Keyscan K-SECURE 1K/4K (36-Bit); Keyscan Mobile Credentials (36-Bit); MiFare Classic (CSN Only)
<b>Shipping Weight</b>	8.5 lbs (3.8 kg)
<b>Housing Construction</b>	Cast zinc alloy (outside housing, levers, and thumbturn), stainless steel inside housing.
<b>Finishes (finish may vary)</b>	626 Satin chrome, 625 Bright Chrome, 606 Satin Brass, 605 Bright Brass, 613 Oil Rubbed Bronze, 618 Bright Nickel, 619 Satin Nickel, U26 Ultra Satin Chrome, U05 Ultra Bright Brass, U06 Ultra Satin Brass, U13 Dark Bronze
<b>Standard Backset</b>	2 3/4" (70mm) backset
<b>Locking options</b>	Cyl, 2 3/4" or 2 3/8" Backset, 1/2" Bolt; Cyl, 2 3/4" Backset, 3/4" bolt Mor, 1 1/4" Faceplate (FP), Utility, w or w-o deadbolt; Mor, 1" FP, LH or RH no deadbolt; Mor, *1" FP, LH or RH w/ deadbolt; For Exit trim options refer to E-Plex Exit Trim in Electronic Lock Price Book.
<b>Batteries</b>	Alkaline batteries (4 AA). Low battery indicator in software and on lock. Battery life up to 1 year (based on optimal usage).
<b>Programming &amp; Audit Trail</b>	Lock memory stores 30,000 audits, max 10,000 users, wireless locks using Aurora software stream lock transactions in real time with on-line programming. Stand-alone lock programming and audit retrieval requires M-Unit.
<b>Programming command card</b>	Command card set matching card technology of lock ordered is required to be purchased separately to program all locks with that same card technology (not included with lock).
<b>Accessibility Standard/Certification</b>	ADA compliant, BHMA/ANSI Grade 1, Florida Windstorm (mortise), UL10/UL10C, ULC S104, FCC Part 15 Class C and CE directive 2014/53/EU and industry Canada compliant.
<b>Operating Conditions</b>	-31°F to 149°F (-35°C to 65°C) 0% to 85% non-condensing humidity at 86°F (30°C).

\*Battery life may vary from application to application, and by operator use.

© 2024 dormakaba Canada, Inc. Information on this sheet is intended for general use only.

**Any questions? We would be happy to advise you.**

Contact us at: 1-888 539-7226