

RCI PSK-3-H







125kHz standard security fob credential



PSK-3-H

RCI PSK-3-H 125kHz standard security fob

RCI Pyramid sets the electronic security benchmark for 125-kHz proximity readers, cards, and tags. Based upon proven contactless digital radio frequency identification (RFID) technology, Pyramid readers interface with a wide range of electronic access control systems by complying with either the legacy Wiegand or the latest bi-directional Open Supervised Device Protocol (OSDP). They offer value-add features such as MAXSecure™ and fleaPower™, and can be ordered to support several proximity card and tag technologies. Additionally, Pyramid cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered to support several proximity reader technologies.

 MAXSecure™ Unique Security Feature	 Warranty Limited Lifetime Warranty	 Wiegand Output Interface	 Slot-Punch Standard Reinforced Brass Eyelet
 Contactless Up to 3.5 in (88 mm)	 Frequency: 125 kHz Read Range: Up to 3.5 inches (88 mm)		

Specifications

PSK-3-H

Technology	Proximity
Frequency	Excitation (125 kHz)
Operation	Passive (no battery)
Type	Key tag
Formats	Wiegand (26-bit)
Material	ABS
Color	Gray
Slot Punch	Standard reinforced brass eyelet
Marking	Date code and ID
Imaging	N/A
Read Range	Up to 3.5 inches (88 mm)
Warranty	Limited lifetime warranty
Dimensions	1.2" W x 1.5" H x 0.15" D (30 mm x 38 mm x 3.8 mm)
Weight	0.16 oz (4.5 g)
Operating Temperature	-35° F to 122° F (-37° C to +50° C)
Humidity	0-95% non-condensing
Technologies Supported	RCI Pyramid; certain HID 125-kHz Proximity protocols supported; certain AWID 125-kHz Proximity protocols supported

NOTES:

Matching internal and external sequential coding standard. If printing, please verify that the printer (or overlay) supports credential type/thickness. Installation scenario may affect read range. Supporting readers include, but are not limited to, P-300-H, P-500-H, P-640-H, P-710-H, P-900-H, PCR35L, PCR620L, PCR640L as well as HID products including ProxPoint® Plus, ThinLine II®, MiniProx®, and MaxiProx.

© 2022 dormakaba Inc. All rights reserved. Pyramid, Ranger & Conekt Series Proximity® are the registered U.S. trademarks of Farpointe Data, Inc. All other trademarks are the property of their respective owners.

dormakaba USA Inc.
6161 E. 75th St.
Indianapolis, IN 46250
800.523.8483
www.dormakaba.us

dormakaba Canada Inc.
7301 Decarie Blvd.,
Montreal QC H4P 2G7
888 539-7226

KAA 1570 08-22