



# HEADERS & GLAZING SYSTEMS

DORMA Headers  
DriFit™ Glazing System  
Floating Header

## DORMA HEADERS

DORMA Header tubes are made to house the RTS overhead concealed closers and a variety of other pivot options. The popularity of concealed overhead closers has led DORMA to furnish fully fabricated headers for every

door and sidelite configuration. The header design allows for a glazing pocket to be snapped into the header tube to permit a seamless transition to the sidelite glazing.

The Dri-Fit™ gasket is used for quick and easy installation. Profiles are available for glass thicknesses of 3/8" (10 mm), 1/2" (12 mm), 5/8" (15 mm), and 3/4" (19 mm) tempered glass.

Two header profiles are available:

- 1-3/4" × 4-1/8" (44 mm × 105 mm)
- 1-3/4" × 4-1/2" (44 mm × 114 mm)

# DORMA DRI-FIT™ SYSTEM

DORMA Dri-Fit™ simplifies glazing installation. The Dri-Fit gasket is used in sidelite rails, header tube glazing pockets, and u-channels.

Dri-Fit sidelite rails are available to match all DRS mechanical profile heights and offer saddle sizes from 1/8" to 3/4" (3 mm to 19 mm) tall.

DORMA also offers the Dri-Fit U-Channel—a low

profile u-channel ideal for glazing with minimal hardware. It can even be recessed in the ceiling and floor to completely eliminate visible hardware.

Five stock finishes are available. Non-stock finishes are available upon request with additional lead time. Extrusions come in stock lengths up to 144" (3658 mm) and 120" (3048 mm) for Brass & Bronze finishes.



## Glass Thickness Availability for Sidelite Rails and DriFit U-Channels<sup>1</sup>

| DRS Sidelite Height / Profile |                                 | 2-1/2" (64) SQ | 2-1/2" (64) TP | 3-5/8" (92) SQ | 3-5/8" (92) TP | 4" (102) SQ | 4" (102) TP    | 6" (152) SQ | 10" (254) SQ   | 1" x 1" (25 x 25) U-Channel | 1" x 1-3/4" (25 x 44) U-Channel | 1-1/4" x 1" (32 x 25) U-Channel | 1-1/4" x 1-3/4" (32 x 44) U-Channel |
|-------------------------------|---------------------------------|----------------|----------------|----------------|----------------|-------------|----------------|-------------|----------------|-----------------------------|---------------------------------|---------------------------------|-------------------------------------|
| Monolithic                    | 3/8" (10 mm)<br>1/2" (12 mm)    | X <sup>2</sup> | X <sup>2</sup> | X              | X              | X           | X <sup>2</sup> | X           | X              | X                           | X                               |                                 |                                     |
|                               | 5/8" (15 mm)<br>3/4" (19 mm)    | X <sup>2</sup> | X <sup>2</sup> | X              |                |             |                | X           | X <sup>2</sup> |                             |                                 | X                               | X                                   |
| Laminated                     | 9/16" (14 mm)<br>11/16" (17 mm) | X <sup>2</sup> | X <sup>2</sup> | X              | X              | X           | X <sup>2</sup> | X           | X              | X                           | X                               | X                               | X                                   |

<sup>1</sup> U-Channel requires wet glazing for proper hold with tempered laminated glass.

<sup>2</sup> Available Fall 2015.

# DORMA FLOATING HEADER

The DORMA Floating Header allows all-glass entrances with transoms to be installed with overhead closers.

The floating header connects to the adjoining sidelite glass—providing a platform for installing overhead closers, magnetic locks, door stops, or walking beam pivots.

- Available in standard architectural metal finishes for single and double door applications, in widths of 4-1/8" or 4-1/2" (105 mm or 114 mm).

- Applications:  
Office  
Retail  
Conference Rooms



DORMA USA, Inc.  
Dorma Drive, Drawer AC  
Reamstown, PA 17567  
800-523-8483  
www.dorma.com