

Raccordement du verrouillage EM

Noir - 0 V DC
Rouge + 12 ou 24 V DC


Contact de verrouillage

Le contact est fermé si le verrouillage EM est alimenté et la contreplaque correctement en place


Noir = Contact (Commun)
Vert = Contact (NO)
Rouge = Contact (NF)

Sélection tension

24 V DC (réglage usine)



12 V DC



Caractéristiques techniques

Alimentation: 12 ou 24 V DC
+20% / -10%

Consommation: 370 mA en 12 V DC
185 mA en 24 V DC

Protection: Par VARISTOR intégrés

Contact: Max 24 V DC et 200 mA



Circuits sensibles à l'électricité statique

F

Wiring details

Black - 0 V DC
Red + 12 or 24 V DC


Door locked contact

The door locked contact is closed if the electromagnet is powered and if the armature plate is correctly in place.


Black = Contact (Commun)
Green = Contact (NO)
Red = Contact (NF)

Voltage selection

24 V DC (factory setting)



12 V DC



Technical data

Power supply: 12 or 24 V DC
+20% / -10%

Current input: 370 mA with 12 V DC
185 mA with 24 V DC

Protection: By integrated VARISTOR

Contact: Max 24 V DC and 200 mA



Static sensitive devices

GB