


Raccordement du verrouillage EM


Sélection tension

F



Relais Verrouillage
Alimentation 12 ou 24 V DC

12 V DC 24 V DC (réglage usine)



Contact de verrouillage

Le contact du relais est fermé si le verrouillage EM est alimenté et la contreplaque est correctement en place.

LED intégrée

LED éteinte: Pas d'alimentation
LED rouge fixe: Pas verrouillée

LED verte : Verrouillée

Caractéristiques techniques

Alimentation: 12 ou 24 V DC
+20% / -10%

Consommation (x2): 500 mA en 12 V DC
250 mA en 24 V DC

Protection: Par VARISTOR intégrés

Contact relais: Max 24 V DC et 2 A




Circuits sensibles à l'électricité statique

Electromagnet connections


Voltage selection

GB



Door locked contacts
Power supply 12 or 24 V DC

12 V DC 24 V DC (factory setting)



Door locked contact

The door locked contact is closed if the electromagnet is powered and if the armature plate is correctly in place.

Integrated LED

LED off: No power supply
LED red: Unlocked

LED green: Locked

Technical data

Power supply: 12 or 24 V DC
+20% / -10%

Current input (x2): 500 mA with 12 V DC
250 mA with 24 V DC

Protection: By integrated VARISTOR

Contact relay: Max 24 V DC and 2 A



Static sensitive devices