

RCI 2 Series

All-in-one strikes



Features

- Versatile strike designed to work with most locks
- Accommodates 1/2" (12.7mm) to 3/4" (19mm) latch projection
- Adjustable deadbolt keeper and deadlatch ramp
- Accommodates up to 1" deadbolt (night-latch function only, bolt will not release)
- Plug-in wire connectors
- Runs cool – solenoid design prevents keeper from heating up
- Trim plate included to cover up irregular frame cut-out
- Stainless steel ensures superior strength and creates a sleek aesthetic
- Includes two keeper shims – 1/16" (1.5mm) and 1/8" (3mm) – for horizontal adjustment for misaligned frames (unique sliding design)
- Non-handed
- Factory tested to over 2-million cycles of operation
- Faceplate 1-1/4"W x 4-7/8H (32mm x 124mm)
- Insert depth: 1-3/4"D (45mm)
- Brushed Stainless Steel (32D) finish

The 2 series are versatile, all-in-one, electric strikes that combine strength and convenience in a sleek design. The RCI F2164 & 2364 strikes feature an adjustable deadbolt keeper and deadlatch ramp allowing them to flexibly work with most locks.



The "Saw-tooth Adjustment Locator" makes installation simple. It allows the installer to move the deadbolt keeper, or plug and deadlatch ramp vertically to align with a wide variety of mortise locks with offset latches. It also includes a trim plate to cover up an irregular frame cut-out. Everything you need for the strike is in the box, including a faceplate for centerline latch entry.

Certifications

- UL 294 Listed for Access Control Unit Accessory (6th Edition)
- UL 1034 burglary-resistant Listed
- UL 10C, 3-hour fire-rating Listed3
- CAN/ULC S104, 3-hour fire-rating Listed3
- California State Fire Marshal Listed (CSFM: 3776-2275:0502)3
- Certified to ANSI/BHMA standard A156.31, Grade 1, endurance 500,000 cycles
- Patent #: US 9,580,935
- Patent #: Canadian 2,850,072



Specifications

 Energy 375mA ¹ Field-selectable 12/24VDC, 12-24VAC ²	 Strength 1,500lb static 70ft-lb dynamic	 Latch monitor Plug-in latch monitor accessory available	 Fire-rated Optional 3-hour Model available ³
 Warranty 10 Year limited warranty	 Mode Fail-secure & fail-safe	 Endurance 500,000 cycles	

¹ Max at 12VDC

² 12-24VAC not available with 2364 model

³ Fire-rated (F) model only, 3-hour for single swing, 90-minutes for standard pair of doors (hollow metal doors only)

Accessories

Model	Description
F2LM	Latch monitor plug-in kit (2A @ 24VDC)
2FP	Filler plate (for use when replacing discontinued 2 Series models)
F2-19	Centerline faceplate, 1-3/8"W x 9"H (35mm x 229mm), 32D finish
F2-29	Offset faceplate, 1-3/8"W x 9"H (35mm x 229mm), 32D finish
SMT-01	Strike marking template kit
940-LG	High profile latch guard, 32D finish

How to order

Options					
F	Fire-Rated ⁴				
	2		64	x	32D
		1	- Fail-Secure		
		3	- Fail-Safe		

Mode

Example: **F2164 x 32D**

⁴Available in fail-secure mode only.

Model	Mode	Volts	Duty	Sound	Amps*	Ohms**
F2164	Fail secure	12VDC	Continuous	Silent	0.375	37
		24VDC			0.190	148
		12-24VAC	Intermittent	Buzz	0.280-0.565	37
2364	Fail safe	12VDC	Continuous	Silent	0.375	37
		24VDC			0.190	148

Intermittent Duty: Energized less than 1 minute with Duty Ratio 1:5 Continuous Duty: Energized 1 minute or more

*Ratings are based on maximum current draw at +10°C and include initial power-up current draw

**Nominal resistance at +25°C ± 7% tolerance

© dormakaba 2024 Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation.

Any questions? We would be happy to advise you.

Contact us at: 1-800-265-6630