

INSTALLATION

910TC-WRM, 910NTC-WRM & 910TC-WRB REMOTE RECEIVERS AND REMOTE TRANSMITTER

The remote module allows wireless activation of the 910TC button for convenience or installations that do not allow for wire access.

1. Remove power to the unit prior to installing the standard or smaller mullion mount remote receivers shown below.



2. Insert the pins of the remote board into the header of the standard or mullion button as indicated below. Ensure the pins are aligned and fully engaged in the header.



3. Reapply power to the unit.

4. Once installed, the transmitter and receiver must be paired to each other for proper operation.

5. On the back of the remote board, locate the button and LED as indicated below.



6. Press and hold the button on the board until the red LED comes on, then release.

7. While the LED is lit, press the button on the transmitter, the LED will blink indicating the code is being stored.



8. The red LED will go out to indicate that storing of the code has been successful.

Up to 5 transmitters can be paired with one receiver by following the above process.

NOTE: Should you need to reprogram or delete a transmitter, all transmitters will be erased and need to be reprogrammed individually.

To Erase All Units: press and hold the button on the back of the board until the red LED comes on. Continue to hold the button until the LED goes out. Repeat steps 6-8 to reprogram

The **Lithium Battery Test Summary** is posted on the 910TC touchless switch product page of the dormakaba.us website under Brochures & data sheets.

FCC Regulatory Statements (For 910TC-WRM and 910TC-WRB)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the Federal Communication Commission (FCC) rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

NOTE: ANY CHANGES OR MODIFICATIONS NOT EXPRESSLY APPROVED BY THE PARTY RESPONSIBLE FOR COMPLIANCE COULD VOID THE USER'S AUTHORITY TO OPERATE THE EQUIPMENT.

910NTC-WRM is compliant to both FCC and ICES requirements.
The appropriate SDOC is available upon request

ISED Regulatory Statements (For 910TC-WRB Only)

This device complies with ISED Canada license-exempt RSS standard(s). Operation is subject to the following two conditions:

- (1) this device may not cause interference, and
- (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme avec ISED Canada applicables aux appareils radio exempts de licence.

L'exploitation est autorisée aux deux conditions suivantes:

- (1) l'appareil ne doit pas produire de brouillage, et
- (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

CAN ICES-3 (B)/NMB-3(B)