

Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

Certificate of constancy of performance 0432-CPR-00026-53

Version 01

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Floor spring door closer BTS 84

Controlled door closing devices for single and doubleleaf swing doors as detailed and classified on annex 1

placed on the market under the name or trade mark of

dormakaba Deutschland GmbH

DORMA Platz 1 58256 Ennepetal Germany

and produced in the manufacturing plant(s)

DO 2.5

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in annex ZA of the standard(s)

EN 1154:1996/A1:2002/AC:2006

under **system 1** for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 11.02.2020 and will remain valid until 11.02.2025 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Dortmund, 11.02.2020

MPA NRW

46

46

Dipl. Ing. Friedrich Head of Certification Body

This Certificate consists of 1 page and 1 annex(es).

The original of this document was issued in German language.

In case of doubt only the German version is valid.





Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

List of Products

Type: "BTS 84"

Description : floor spring door closer with hydraulic damping, adjustable second

closing area and fix sizes.

Size:

Classification / mounting: 3 8 3 1 1 4

Manufacturing plant : DO 2.5

Remarks:

Intended use:

For single and double leaf fire- and/or smoke swingdoors

Essential characteristics	Clauses with requirements in EN 1154:1996/A1:2002/AC:2006	Performance of product
Self-closing	5.2.1 General	passed
, .	5.2.3 Closing torque	passed (Size 3)
	5.2.4 Opening torque	passed (Size 3)
	5.2.5 Efficiency	passed (Size 3)
	5.2.6 Closing time	passed (Size 3)
	5.2.7 Opening angle	passed (Class 3)
	5.2.8 Overload test	passed (Size 3)
	5.2.9 Temperature dependence	passed (Size 3)
	5.2.10 Leakage	passed
	5.2.11 Damage	passed
	5.2.12 Latch regulation	not applicable
	5.2.13 Back check	not applicable
	5.2.14 Delayed action	not applicable
	5.2.15 Adjustable force	not applicable
	5.2.16 Free play at zero point position	passed (Size 3)
	5.2.18 Use on fire-/smoke protection doors	Class 1: passed
Durability	5.2.2 Durability	Class 8 (500 000 cycles): passed
Self-closing	5.2.17.1 Corrosion resistance	Class 4 (240h): passed
	5.2.17.2 Corrosion resistance	Class 4 (240h): passed
	5.2.17.3 Corrosion resistance	Class 4 (240h): passed
Dangerous substances	Annex ZA.3	The manufacturer has not declared any dangerous substances.



Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

Type: "BTS 84"

Description: floor spring door closer with hydraulic damping, adjustable second

closing area and fix sizes.

Size:

Classification / mounting: 3 8 4 1 1 4

Manufacturing plant: DO 2.5

Remarks:

Intended use:

For single and double leaf fire- and/or smoke swingdoors

Essential characteristics	Clauses with requirements in EN 1154:1996/A1:2002/AC:2006	Performance of product
Self-closing	5.2.1 General	passed
, ,	5.2.3 Closing torque	passed (Size 4)
	5.2.4 Opening torque	passed (Size 4)
	5.2.5 Efficiency	passed (Size 4)
	5.2.6 Closing time	passed (Size 4)
	5.2.7 Opening angle	passed (Class 3)
	5.2.8 Overload test	passed (Size 4)
	5.2.9 Temperature dependence	passed (Size 4)
	5.2.10 Leakage	passed
	5.2.11 Damage	passed
	5.2.12 Latch regulation	not applicable
	5.2.13 Back check	not applicable
	5.2.14 Delayed action	not applicable
	5.2.15 Adjustable force	not applicable
	5.2.16 Free play at zero point position	passed (Size 4)
	5.2.18 Use on fire-/smoke protection doors	Class 1: passed
Durability	5.2.2 Durability	Class 8 (500 000 cycles): passed
Self-closing	5.2.17.1 Corrosion resistance	Class 4 (240h): passed
	5.2.17.2 Corrosion resistance	Class 4 (240h): passed
	5.2.17.3 Corrosion resistance	Class 4 (240h): passed
Dangerous substances	Annex ZA.3	The manufacturer has not declared any dangerous substances.