

# Keyscan SRK Reader series

Integrated solutions for unique 'back-of-the-house' access control applications



## Integrated solutions for complete access control

The Keyscan SRK reader series is designed for dormakaba Multihousing or Lodging access control applications integrating with Keyscan networked access control systems. The integration offers a single-credential solution with many unique features for complete access control throughout a property.

Only these SRK readers will decrypt and read both dormakaba's hospitality credential formats as well as Keyscan credential formats. This allows property managers and administrators to utilize Keyscan Aurora software to program unique back-of-the-house access control

applications affecting common areas, elevator floors, and perimeter access control such as parking gate or garage entrances.

The SRK reader series is available in three different models to suit a number of installation requirements and each offering a sleek minimalist design to compliment any property décor. They may only be purchased from dormakaba Canada.

### Back-of-house applications:

- **SRK-RCFN0:** the reader is designed to be installed in or behind a third-party decorative wall plate.
- **SRK-RNFC0:** the single-gang style reader is installed using a flush mount wall plate, available in various finishes.
- **SRK RNSC0:** a mullion-style reader is installed on a surface mount or on an aluminum door or entrance frame.

The readers are also available in BLE-ready models for BlueSky applications.

### SRK-RCFN0 Specifications

Size	1.75"W x 2.8125"L x 0.8125"D (4.4 cm x 6.7 cm x 2.1 cm) (excludes mounting bracket)
Availability	Must be purchased from dormakaba Canada; these readers are NOT available through distribution
Input voltage	12 VDC at reader
Current draw	200mA (maximum) - idle current 10mA
Operating temperature	-35 F to 123° F (-37° C to 51° C)
Cable	6 conductor shielded 22 AWG; Wiegand interface; 500 feet (152 meters) maximum
Weight	3.2 oz (90.7 g)
Firmware requirement	Keyscan CA150 - PC1156 with custom firmware CF10010 V1.63 Keyscan CA & EC series - PC1097 with custom firmware CF10004
BLE	Model SRK-RCFN2*



### SRK-RNFC0 Specifications

Size	1.75"W x 2.8125"L x 0.8125"D (4.4 cm x 6.7 cm x 2.1 cm) (excludes mounting bracket)
Availability	Must be purchased from dormakaba Canada; these readers are NOT available through distribution
Input voltage	12 VDC at reader
Current draw	200mA (maximum) - idle current 10mA
Operating temperature	-35 F to 123° F (-37° C to 51° C)
Cable	6 conductor shielded 22 AWG; Wiegand interface; 500 feet (152 meters) maximum
Weight	3.2 oz (90.7 g)
Firmware requirement	Keyscan CA150 - PC1156 with custom firmware CF10010 V1.63 Keyscan CA & EC series - PC1097 with custom firmware CF10004
BLE	Model SRK-RCFN2*



### SRK-RNSC0 Specifications

Size	1.75"W x 2.8125"L x 0.8125"D (4.4 cm x 6.7 cm x 2.1 cm) (excludes mounting bracket)
Availability	Must be purchased from dormakaba Canada; these readers are NOT available through distribution
Input voltage	12 VDC at reader
Current draw	200mA (maximum) - idle current 10mA
Operating temperature	-31° F to 151° F (-35° C to 66° C) / Meets IP54 rating
Cable	6 conductor shielded 22 AWG; Wiegand interface; 500 feet (152 meters) maximum
Weight	3.2 oz (90.7 g)
Firmware requirement	Keyscan CA150 - PC1156 with custom firmware CF10010 V1.63 Keyscan CA & EC series - PC1097 with custom firmware CF10004
BLE	Model SRK-RCFN2*



Copyright © 2024 dormakaba Inc. Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation. \*These BLE readers will require on-site programming of customers BLE site code in each BLE reader before use by customer. Requires M-Unit (HH6) programmer and Comm-71800-1 programming cable. Programming done by dormakaba certified integrator during product commissioning.

**Any questions? We would be happy to assist.**  
Contact us at: 800-265-6630