



NOTES:

1. DO NOT SCALE DRAWING.
2. DIMENSIONS ARE IN INCHES/(MM).
3. CAUTION: SEX NUTS ARE REQUIRED FOR ATTACHMENT OF COMPONENTS TO UNREINFORCED DOORS AND TO WOOD OR PLASTIC FACED COMPOSITE TYPE FIRE DOORS, UNLESS AN ALTERNATIVE METHOD IS IDENTIFIED IN THE INDIVIDUAL DOOR MANUFACTURER'S LISTINGS.
4. CAUTION-DORMA RECOMMENDS FRAME REINFORCEMENT (BY OTHERS) TO BE SUPPLIED AND IN PLACE BEFORE FRAME IS INSTALLED.
5. TEMPLATE FOR 4-1/2" X 4-1/2" BUTT HINGES AND 3/4" OFFSET PIVOTS.
6. MINIMUM DOOR WIDTH 32".
7. HOLD OPEN RANGE 80°-125°.
8. MAXIMUM OPENING 170°.
9. RIGHT HAND DOOR SHOWN

DOOR CLOSER MODELS: TS93 EMR/T
 TRACK INSTALLATION (PULL SIDE MOUNT)
 WITH SMOKE DETECTOR

DORMA USA, Inc.
 Reamstown, PA 17567

Toll-Free: (800) 523-8483
 Facsimile: (800) 274-9724

Always consult DORMA's web site for latest
 template at www.dorma.com.