



Combi B30 safe lock

Proven reliability, high flexibility, high end design

Electronic combination dead bolt lock with mechanical redundancy. Especially suitable for of the class CEN III-V safes. In addition to a timeless, flat and user-friendly design, the lock provides a significantly increased range of functions.

The keyboard and the button of the input unit are designed so that you determine the mounting position yourself. The mounting can be done both horizontally and vertically. A customer logo on the knob is optionally available.

Mechanical redundancy

The integrated mechanic redundancy offers maximum reliability: by removing the rotary handle the hidden keyhole can be exposed and the lock can be opened with the double bitted key.

Software

Furthermore, a PC software is available to read the Audit of the lock or to execute easily all programming steps of the lock.

dormakaba Schweiz AG

Mühlebühlstrasse 23
8620 Wetzikon

T: +41 44 931 61 11
www.dormakaba.com

Code functions

- 3 hierarchical levels: 1 master, 30 users, 1 courier
- Dual mode for opening selectable
- Code disabling
- Duress code selectable
- Penalty after four incorrect codes

Authorizations

- Courier bypasses time delay
- Input to override the Dual Mode

Opening delay

- Opening delay definable 0 ... 99 minutes
- Confirmation window definable 1 ... 19 minutes
- Input for overriding Time delay

Option alarmbox

- Remote disabling
- Silent alarm
- Lock monitoring
- Monitoring contact
- Bolt work contact
- Sabotage line
- Door contact

Approvals

- EN 1300
- VdS class 2
- IMP
- A2P

Accessories

Alarm Box

- VdS alarm box for connection to an EMEA.

External plug-in power supply units

- Plug-in power supply for the direct power supply (EU, 100-240V / 50-60Hz / 9V)
- Plug-in power supply for the power supply via the alarm box (EU, 100-240V / 50-60Hz / 12V)

Bolt work handle

- Bolt work handle chrome plated with bearing bush and rosette chrome plated
- Bolt work handle chrome plated with bearing bush without rosette

Connection cable

- Connection cable lock - alarm box 100/300 cm.

Functional Scope

Lock

- Deadbolt lock
- Mechanical redundancy for emergency openings
- Bolt sensor monitored
- 1 floating input 12 VDC
- 1 potential-free output
- 200 Audit events
- External power supply optional
- Different key lengths
- Detachable key part and foldable key part available

Input unit

- High quality metal input unit with PC interface
- Powder-coated colour versions or shiny chrome, matt or golden
- Battery operation (2 x UM4, AAA, LR03)
- Customised logo optional
- Can be mounted horizontally or vertically

Alarmbox

- Closure monitoring line
- Opening Line of Control
- Cover contact for sabotage monitoring
- Power supply 9 to 15 VDC

Software

- Direct connection to the lock
- Programming software:
 - Comfortable programming
 - Access control by USB Secure dongle
 - Reading out the event memory
 - Audit optional with time and date stamp
- Audit Software:
 - Reading out the event memory
 - Audit optional with time and date stamp
- Windows operating systems (32/64 bit) W7 and newer

