



Example 9 0 2 0 0 0 0 - 2 6 D - 4 1

MODEL OPTIONS FINISH PACKAGING

Build the model number with the required functions/finishes.
For pricing information and lead-times, please contact sales.gb@dormakaba.com
Options in Blue text denote common/popular configurations

Standard Model	Description
9190000-26D-41	Auxiliary Lock with Thumbturn, 5/8" (16 mm) Deadlocking Spring Latch, flat front, 1 3/4"-2 1/8" (44 mm-54 mm) thick, latch holdback

Choose One Option from This Category

Model Options	Description
02	1" (25 mm) Deadbolt Latch, 1 3/8"-1 1/2" (35 mm-38 mm) thick
04	1" (25 mm) Deadbolt Latch, 1 3/4"-2 1/8" (44 mm-54 mm) thick
06	1" (25 mm) Deadbolt Latch, 1 3/8"-1 1/2" (35 mm-38 mm) thick, key override
10	1" (25 mm) Deadbolt Latch, 1 3/4"-2 1/8" (44 mm-54 mm) thick, key override
17	5/8" (16 mm) Deadlocking Spring Latch, flat front, 1 3/8"-1 1/2" (35 mm-38 mm) thick, latch holdback
19	5/8" (16 mm) Deadlocking Spring Latch, flat front, 1 3/4"-2 1/8" (44 mm-54 mm) thick, latch holdback
20	5/8" (16 mm) Deadlocking Spring Latch, flat front, 1 3/8"-1 1/2" (35 mm-38 mm) thick, no latch holdback
22	5/8" (16 mm) Deadlocking Spring Latch, flat front, 1 3/4"-2 1/8" (44 mm-54 mm) thick, no latch holdback
27+	5/8" (16 mm) Deadlocking Spring Latch, flat front, 1 3/8"-1 1/2" (35 mm-38 mm) thick
29+	5/8" (16 mm) Deadlocking Spring Latch, flat front, 1 3/4"-2 1/8" (44 mm-54 mm) thick
35*	5/8" (16 mm) Deadlocking Spring Latch, flat front, 1 3/8"-1 1/2" (35 mm-38 mm) thick, latch holdback, key override
38*	5/8" (16mm) Deadlocking Spring Latch, flat front, 1 3/4"-2 1/8" (44 mm-54 mm) thick, latch holdback, key override

* D.O.D. Compliant

*Key override orders will consist of all locks on the order being keyed alike, unless there is a specific key cut called out or the locks on the order are requested to be keyed differently.

Simplex[®]

900 Series

Choose up to Four Options - Insert 0 if Less than Four Options are required.

Options	Description
1	Substitutes a surface-mounted strike box for metal door frames in place of the standard strike box (part number 74464) (see 900 Series Accessories—Adapter Kit)
2	Deletes the key cylinder from key override models. Recessed escutcheon recommended for standard rim cylinder installation. Rim cylinder tailpiece must be reduced in width to accommodate the tail receptacle. Specify the position of the cylinder tailpiece (vertical or horizontal) to mate with the standard size rim cylinder (not supplied).
3	Substitutes a 2½" (64 mm) lever in place of the standard inside thumbturn (part number 74437) (cannot be used with option 5)
4*	Master Keyed (key override models)
5	Adds the panic bar release kit to a spring latch model (part number 74438) (cannot be used with option 3) - <i>Installer is responsible for undertaking any 3rd party certifications</i>
6	Deletes latch holdback (935 and 938 models)
7	Deletes the key cylinder from key override models and changes gear plate to a 100 Series. Recessed escutcheon recommended for standard rim cylinder installation. The rim cylinder tailpiece must be reduced in width to accommodate the tail receptacle. Specify the position of the cylinder tailpiece (vertical or horizontal) to mate with the standard size rim cylinder (not supplied).
8	Changes gear plate to accept a horizontal tailpiece
Finish Options	Description
26D	Satin Chrome (Powder Paint) Standard Finish
04**	Satin Brass (Powder Paint)

Notes

* D.O.D. Compliant

** 04 Finish not available on Model 927/929

*Key override orders will consist of all locks on the order being keyed alike, unless there is a specific key cut called out or the locks on the order are requested to be keyed differently.

dormakaba UK & Ireland
Lower Moor Way
Tiverton
Devon
EX16 6SS

T: +44 (0)870 000 5625
E: info.gb@dormakaba.com

www.dormakaba.co.uk