

RCI WRT-2+H & WRT-4+H

long-range transmitters



RCI WRT-2+H & WRT-4+H long-range transmitters

RCI Ranger sets the electronic security benchmark for high frequency, long-range identification receivers and transmitters. Based upon proven contactless digital ultra high frequency (UHF) technology, the RCI Ranger receivers interface with a wide range of electronic access control systems by complying with either the legacy Wiegand communication protocol or the latest bi-directional Open Supervised Device Protocol (OSDP). Additionally, RCI Ranger transmitters are active devices, powered by the most reliable and common battery, and equipped with a potted proximity or contactless smartcard module. The modules can be ordered to support several proximity reader technologies and allow the transmitter to be used as a close-range credential.



MAXSecure™
Unique Security Feature



ETL Listed
Independently Tested and
Certified Conforms to UL
Standard 294 and ULC 60839-11-1



Warranty
One-Year Warranty



**Wiegand
Output
Interface**



Built-in Eyelet
Carry on a Key Ring



Contactless
Up to 200 ft (61 m) Presentation
– Up to 3.5 in (88 mm)



Button Press Frequency: 433 MHz
Read Range: Up to 200 feet (61 m)
Presentation Frequency: 125 kHz
or 13.56 MHz Read Range: Up to
3.5 inches (88 mm)

Specifications

WRT-2+H & WRT-4+H

Technology	Long range
Frequency	Button press – 433 MHz Presentation – 125 kHz or 13.56 MHz
Marking	Date code and ID
Dimensions	1.45" W x 2.5" H x 0.56" D (37 mm x 63.5 mm x 14.2 mm)
Button Press Transmission	Rolling code + encryption
Weight	0.7 oz (20 g)
Certifications	FCC, ICC, CE, UL Standard 294, ULC 60839-11-1
IP Code	IP67-rated for outdoor use
Battery	Single replaceable CR2032, 3.3V, lithium battery
Compatibility	Button press: WRR-44 and WRR-22 Receivers; Presentation: Pyramid readers and others
Read Range	Button press: Up to 200 feet (61 m); Presentation: Up to 3.5 inches (88 mm)
Durability	Electronics sealed in a weather-resistant enclosure
Interface	Wiegand (26-bit industry standard)
Operating Temperature	-40° F to 122° F (-40° C to +50° C)
Enclosure Color	Black polycarbonate enclosure with gray ABS keys
Key Ring	Optional 1-inch (25 mm) key ring
Warranty	1 Year limited
LED	Integrated red LED standard (activated upon button press)
Transmitters Models	WRT-2+ (2 buttons labeled 1 & 2); WRT-4+ (4 buttons labeled 1 through 4)
Interoperability	WRT-2+H or WRT-4+H: Supports certain HID® 125-kHz Proximity protocols WRT-2+D2 or WRT-4+D2: Supports certain MIFARE® DESFire® EV2 2K 13.56-MHz Smartcard protocols

NOTES:

Carrying the ETL Label and tested by Intertek, conforms to UL Standard 294 and ULC Standard 60839-11-1. Independently tested and verified by Intertek. Rated to typically provide more than 250,000 button presses under normal conditions. Button press tested with 12 VDC at WRR-44, presentation with 12 VDC at P-500-H-A. Receiver coverage is omni-directional and need not be installed in a line-of-sight configuration. Electronics are snap sealed in a weather-resistant enclosure. When ordering, please indicate the proximity insert compatibility desired by using a suffix, for example, WRT-4+H. Contact your representative for additional information. Supports readers including, but are not limited to, P-300-H-A, P-500-H-A,, and P-640-H-A, P-710-H-A and P-900-H-A as well as PCR and CSR Series and HID ProxPoint® Plus, ThinLine II®, MiniProx® ProxPro and MaxiProx.

© 2022 dormakaba Inc. All rights reserved. Pyramid, Ranger & Conekt Series Proximity® are the registered U.S. trademarks of Farpointe Data, Inc. All other trademarks are the property of their respective owners.



dormakaba USA Inc.
6161 E. 75th St.
Indianapolis, IN 46250
800.523.8483
www.dormakaba.us

dormakaba Canada Inc.
7301 Decarie Blvd.,
Montreal QC H4P 2G7
888 539-7226

KAA1582 08-22