

RCI PSK-3-H







125kHz standard security fob credential



RCI PSK-3-H 125kHz standard security fob

RCI Pyramid sets the electronic security benchmark for 125-kHz proximity readers, cards, and tags. Based upon proven contactless digital radio frequency identification (RFID) technology, Pyramid readers interface with a wide range of electronic access control systems by complying with either the legacy Wiegand or the latest bi-directional Open Supervised Device Protocol (OSDP). They offer

value-add features such as MAXSecure™ and fleaPower™, and can be ordered to support several proximity card and tag technologies. Additionally, Pyramid cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered to support several proximity reader technologies.

	MAXSecure™ Unique security feature		Warranty Limited lifetime warranty		Wiegand Output interface
	Slot-punch Vertical & horizontal indicators		Contactless Up to 2.5 in (64 mm)		Frequency: 125 kHz Read range: Up to 3.5 inches (88 mm)

Specifications – PSK-3-H

Technology	Proximity
Frequency	Excitation (125 kHz)
Operation	Passive (no battery)
Type	Key tag
Formats	Wiegand (26-bit)
Material	ABS
Color	Gray
Slot punch	Standard reinforced brass eyelet
Marking	Date code and ID
Imaging	N/A
Read range	Up to 3.5 inches (88 mm)
Warranty	Limited lifetime warranty
Dimensions	1.2" W x 1.5" H x 0.15" D (30 mm x 38 mm x 3.8 mm)
Weight	0.16 oz (4.5 g)
Operating temperature	-35° F to 122° F (-37° C to +50° C)
Humidity	0-95% non-condensing
Technologies supported	RCI Pyramid; certain HID 125-kHz Proximity protocols supported; certain AWID 125-kHz Proximity protocols supported

NOTES:

Matching internal and external sequential coding standard. If printing, please verify that the printer (or overlay) supports credential type/thickness. Installation scenario may affect read range. Supporting readers include, but are not limited to, P-300-H, P-500-H, P-640-H, P-710-H, P-900-H, PCR35L, PCR620L, PCR640L as well as HID products including ProxPoint® Plus, ThinLine II®, MiniProx®, and MaxiProx.

Any questions? We would be happy to advise you.

Contact us at: 1-800-265-6630