



Package Width	Rough Opening Width	Clear Slide Opening	Door Panel Width	Breakout Width
(8'-6") 102" [2591]	102 1/2" [2604]	39 5/8" [1006]	25 7/8" [657]	46 7/8" [1191]
(9'-0") 108" [2743]	108 1/2" [2756]	42 5/8" [1083]	27 3/8" [695]	49 7/8" [1267]
(10'-0") 120" [3048]	120 1/2" [3061]	48 5/8" [1235]	30 3/8" [772]	55 7/8" [1419]
(12'-0") 144" [3658]	144 1/2" [3670]	60 5/8" [1540]	36 3/8" [924]	67 7/8" [1724]
(14'-0") 168" [4267]	168 1/2" [4280]	72 5/8" [1845]	42 3/8" [1076]	79 7/8" [2029]
(16'-0") 192" [4877]	192 1/2" [4890]	84 5/8" [2149]	48 3/8" [1229]	91 7/8" [2334]
Width Formulas	Package Width + 1/2" [13]	(Package Width / 2) - 11 3/8" [289]	(Package Width / 4) + 3/8" [10]	(Package Width / 2) - 4 1/8" [105]

- This Standard Bi-part door package consists of:
 - Panels:
 - 2 5/8" [67] Narrow stile door panels (including 3/4" [19] wide glass stop).
 - 3-1/4" [83] Optional muntin mounted at 41-3/4" [1060] centerline on all panels (including 3/4" [19] wide glass stop).
 - 4" [102] Bottom rails (including 3/4" [19] wide glass stop).
 - 1 3/4" [44] x 4 1/2" [114] Double pocket jambs.
 - Vertical and horizontal brush type weather stripping (AAMA-701-11Class A).
 - Recessed pull handle on SX panel.
 - 3/4" [19] wide snap-in glass stops for glazing from 1/4" [6] to 1 1/4" [32] thick at 1/8" [3] increments.
 - ITS Hydraulic self-closer in SX panels.
 - Breakaway sliding door panels (SX) and fixed sidelights (O) panels.
 - Finishes:
 - Clear anodized (BHMA 204).
 - Dark Bronze anodized (BHMA 313).
- Typical Package Options:
 - Finishes: special anodized, PVDF (wet) paint, powder coat, and cladding available for header, panels and jambs.
 - Muntins: multiple muntins, various heights and locations.
 - Bottom Rails: 7" [178], 10" [254]. Other options available.
 - Santoprene rubber weather stripping available.
 - Locking and Security Options:
 - Manual two point mortise lock with thumb turn and key cylinder.
 - Security contacts.
 - Jambs: 1 3/4" [44] x 4 1/2" [114] and 2" [51] x 6" [152] smooth available.
- Dimensions:
 - Drawing dimensions are in English & Metric units. Metric units are displayed as: 1" [25] millimeters.
 - Typical package dimensions: (Glass thickness may be limited by panel size)
 - Each door package is manufactured to your custom size requirements.
 - Package Width: Min. 8'-6" [2591] to Max. 16' [4877].
 - Header Height: Min. 7' [2134] to Max. 9' [2743]
 - SX Panel Weight: Max. Weight 200 lbs [90kg].
- Standards of Compliance:
 - Designed to comply with these standards depending on installation and application:
 - International Building Code (Section 1008).
 - NFPA 101 Life Safety Code (Section 7.2.1.9).
 - Refer to Local, State, National or AHJ. Building Code for minimum door height and minimum/maximum width allowable for egress requirements.
 - Minimum ADA is 32" clear slide opening.
- Contact dormakaba Architectural Services for more information:
 - Phone: 1-844-SPEC-NOW (1-844-773-2669)