



Nightlatch - NL Series

KCS - Kaba Commercial Series

The Kaba NL Nightlatch is a high quality, commercial nightlatch.

Standard Features

Stainless steel case and strike. Case dimensions: 95mm x 68mm x 22mm. Latchbolt: 12mm projection, reversible.

Door Thickness

NL Series locks are suitable for doors 35mm minimum to 46mm maximum thickness.

Keying

Supplied less cylinder. 121 rim cylinder ordered separately.

Fire Rated

The NL550 nightlatch lock is fire rated and complies with Australian Standard AS1905-1-2005 Part 1.



Finishes

Satin Stainless Steel SSS

Nightlatch

NL Series - functions


NL450 RIM LATCH WITH SNIB

OUTSIDE

Operated by key from outside. Except when internal snib is activated for nightlatch function.

INSIDE

Operated by turn. Latchbolt may be held back or nightlatch function activated by snib. When snib activated from inside, it cannot be opened by turn inside or key from outside



PRODUCT CODE
NL450SSS

NL550 RIM LATCH LESS CYLINDER

OUTSIDE

Operated by key from outside.

INSIDE

Operated by turn from inside. Latchbolt can not be held back or deadlocked.



PRODUCT CODE
NL550SSS





Nightlatch- RNL Series

KRS - Kaba Residential Series

The Kaba RNL Nightlatch is a premium quality, residential nightlatch.

Standard Features

- ANSI Grade 3
- Only available in a display pack

Door Thickness

RNL Series locks are suitable for doors 35mm minimum to 46mm maximum thickness.

Keying

Supplied in C4 5 pin.
121 cylinder ordered separately for restricted systems.

Nightlatch

RNL Series - functions


RNL RIM LATCH WITH SNIB

OUTSIDE

Operated by key from outside. Operated by key from outside. Except when internal snib is activated for nightlatch function.

INSIDE

Operated by turn. Latchbolt may be held back or nightlatch function activated by snib. When snib activated from inside, it cannot be opened by turn inside or key from outside.



PRODUCT CODE
DISPLAY PACK
RNLDP