



Package Width	Rough Opening Width	Clear Slide Opening	Door Panel Width	Breakout Width
(9'-0") 108" [2743]	108 1/2" [2756]	49 1/16" [1246]	25 11/16" [652]	98 13/16" [2510]
(10'-0") 120" [3048]	120 1/2" [3061]	55 1/16" [1399]	28 11/16" [729]	110 13/16" [2815]
(12'-0") 144" [3658]	144 1/2" [3670]	67 1/16" [1703]	34 11/16" [881]	134 13/16" [3424]
(14'-0") 168" [4267]	168 1/2" [4280]	79 1/16" [2008]	40 11/16" [1033]	158 13/16" [4033]
(16'-0") 192" [4877]	192 1/2" [4890]	91 1/16" [2313]	46 11/16" [1186]	182 13/16" [4643]
Width Formulas	(Package Width) + 1/2" [13]	(Package Width / 2) - 4 15/16" [125]	(Package Width / 4) - 1 5/16" [33]	(Package Width) - 9 3/16" [233]

- This Standard Bi-part Fine Frame door package consists of:
  - Operator:
    - Two combination motion/presence sensors (one on each side) (See sensor options page).
    - ESA II motor drive unit with self-learning and self-monitoring microprocessor controller.
    - Jamb mounted 5 function rocker switch panel (see mode switch options page).
  - Panels:
    - 3-7/16" [88] Bottom rails.
    - 1 3/4" [44] x 4 1/2" [114] Double Pocket jambs.
    - Vertical and horizontal brush type weather stripping (AAMA-701-11Class A).
    - Floor Bolt Lock, one per SX panel (threshold required).
    - ADA compliant surface applied track and threshold 1/2" [13] x 4 1/2" [114].
    - Emergency Breakaway sliding door panels (SX) and breakaway sidelights (SO) panels.
    - 3/8" [10] thick Clear Tempered Float Glass factory glazed panels.
  - Finishes:
    - Clear anodized (BHMA 204).
    - Dark Bronze anodized (BHMA 313).
- Optional Transom:
  - Single vertical 1 3/4" [44] x 4 1/2" [114] double pocket mullion (Standard). Multiple verticals available.
  - Glass thickness options 1/4" [6] thru 1-1/4" [32] at 1/8" [3] increments.
  - 1/4" [6] Glass uses pocketed tubes and pressed in-glazing, top and sides.
  - Other glass thickness use snap-in sash on all sides.
- Typical Package Options:
  - Finishes: special anodized, PVDF (wet) paint, powder coat, and cladding available. header, panels and jambs only.
  - Santoprene rubber weather stripping available.
  - Locking and Security Options:
    - Bi-stable Autolock sliding carrier lock concealed in header.
    - DG1000 type exit device (SX panels).
  - Jambs: 1 3/4" [44] x 4 1/2" [114] and 2" [51] x 6" [152] smooth available.
- Drawing Notes:
  - Drawing dimensions are in English & Metric units. Metric units are displayed as: 1" [25] millimeters.
  - Package Dimensions: (May be limited by panel weight):
    - Each door package is manufactured to your custom size requirements.
    - Package Width: Min. 9' [2743] to Max. 16' [4877].
    - Header Height: Min. 7'-4 1/2" Max. 10' [3048].
    - Package Height: Max. 12' [3658] with Transom.
    - SX and SO Panel Weight: Max. 225 lbs [102 kg].
  - Maximum special application limits / custom packages: (Sizes may be restricted due to complexity and application). (Please contact dormakaba Architectural Services for dimensions outside of typical sizes above)
    - Package Width: Min. 9' [2743] to Max. 18' [5486].
    - Package Height: Max. 12' [3658].
    - Header Height: Max. 10' [3048].
    - Transom Height: Min. 8" [203] to Max. 2' [610].
    - SX and SO Panel Width: Max. 54" [1219].
    - SX Panel Size Limit = (SX Panel Width x Weight) < 900 ft-lbs [1220 N-m] Max.
- Power Requirements:
  - 120V +/- 10%, 50/60 Hz, 6.6A peak, 250 W. Up to 4 operators on a single 20A breaker. Service to header by electrician.
- Standards of Compliance:
  - UL 325 & CSA 22.2 (listed with ETL).
  - Designed to comply with these standards depending on installation and application:
    - International Building Code (Section 1008).
    - ANSI/ BHMA 156.10.
    - ANSI/ BHMA 156.38.
    - NFPA 101 Life Safety Code (Section 7.2.1.9).
  - Refer to Local, State, National or AHJ. Building Code for minimum door height and minimum/maximum width allowable for egress requirements.
  - Minimum ADA is 32" clear slide opening.
- Contact dormakaba Architectural Services for more information:
  - Phone: 1-844-SPEC-NOW (1-844-773-2669)

ESA400\_B

Sheet 1 of 1

**dormakaba**

1 Dorma Drive, Reamstown PA 17567 Phone: 717-336-3881

Drawing Title: **ESA400 AUTOMATIC SLIDING DOOR**

**FULL BREAKOUT BI-PART FINE FRAME**

© dormakaba Subject to Change Without Notice. Date: 5-JUL-2022