dormakaba

RCI MEM2400 Compact electromechanical lock



Features

- Patented electromagnetic lock with early warning detectors
- Bi-color LED light indicates l ock status
- Compact surface-mount design
- Includes adjustable L & Z bracket
- Capable of releasing under door back pressure (pre-load) of up to 150lbs (70kg)
- Aluminum extrusion casing and anodized coated, high grade zinc plating on magnet and plate
- No residual magnetism
- Low energy consumption



Energy 350mA1 Field-selectable 12/24VDC



Warranty

3 Year limited warranty

¹At 12VDC, 175mA at 24VDC



Strength 1,500lbf Holding force



Monitor Lock & door status sensors

For inswing doors & small enclosures.

Applications	Dimensions	
• Buildings	8-5/8"W x 1-7/16"H x 1-3/8"D (218mm x 36mm x 35mm)	
• Hotels	Armature plate:	
• Lockers	7-1/8"W x 1-3/16"H x 1/2"D (181mm x 30mm x 12.5mm)	
 Cabinets 		

Specifications

Voltage	Current	Duty	
12VDC	350mA1	Continuous	
24VDC	175mA	Continuous	
¹ At 12VDC, 175mA at 24VDC			

Copyright © 2024 dormakaba Canada Inc. Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation.

Any questions? We would be happy to advise you. Contact us at: 1-800-265-6630