



Package Width	Rough Opening Width	Clear Slide Opening	Door Panel Width	Egress Width
(8'-0") 96" [2438]	96 1/2" [2451]	38 1/4" [972]	24 3/8" [619]	43 3/4" [1111]
(10'-0") 120" [3048]	120 1/2" [3061]	50 1/4" [1276]	30 3/8" [772]	55 3/4" [1416]
(12'-0") 144" [3658]	144 1/2" [3670]	62 1/4" [1581]	36 3/8" [924]	67 3/4" [1721]
(14'-0") 168" [4267]	168 1/2" [4280]	74 1/4" [1886]	42 3/8" [1076]	79 3/4" [2026]

This table represents common package sizes. Each door package is manufactured to your custom size requirements.

- This Surface Applied All Glass Bi-part door package consists of:
  - Operator:
    - Two combination motion/presence sensors (one on each side) (See sensor options page)
    - ESA II motor drive unit with self-learning and self-monitoring microprocessor controller.
    - Jamb mounted 5 function rocker switch panel (see mode switch options page).
  - Panels:
    - 6" [152] Bottom rails.
    - 1 3/4" [44] x 4 1/2" [114] Double Pocket jambs.
    - Vertical and horizontal brush type weather stripping (AAMA-701-11Class A).
    - ADA compliant surface applied track and threshold 1/2" [13] x 4 1/2" [114].
    - Single point bottom rail mounted mortise lock (full threshold required).
    - Breakaway sliding door panels (SX) and vertical pocket tubes (P).
    - 1/2" [13] tempered float glass (not supplied with door).
  - Finishes:
    - Clear anodized (BHMA 204).
    - Dark Bronze anodized (BHMA 313).
- Typical Package Options:
  - Finishes: special anodized, PVDF (wet) paint, powder coat, and cladding available. header, panels and jambs only.
  - Locking and Security Options:
    - Bi-stable Autolock sliding carrier lock concealed in header (only prevents sliding).
  - Jambs: 1 3/4" [44] x 4 1/2" [114] and 2" [51] x 6" [152] smooth available.
- Drawing Notes:
  - Drawing dimensions are in English & Metric units. Metric units are displayed as: 1" [25] millimeters.
  - Package Dimensions (May be limited by panel weight):
    - Each door package is manufactured to your custom size requirements.
    - Package Width: Min. 7'-6" [2286] to Max. 16' [4877].
    - Header Height: Min. 7'-4 1/2" Max. 8' [2438].
    - SX Panel Weight: Max. 225 lbs [102 kg].
  - Maximum special application limits: (Sizes may be restricted due to complexity and application) (Please contact Dorma Architectural Services for dimensions outside of typical sizes above).
    - Package Width: Min. 7'-6" [2286] to Max. 21' [6401].
    - Header Height: Max. 11' [3353].
    - SX Panel Width: Max. Width 56" [1422].
    - SX Panel Size Limit = (SX Panel Width x Weight) < 900 ft-lbs [1220 N-m] Max.
- Power Requirements:
  - 120V +/- 10%, 50/60 Hz, 6.6A peak, 250 W. Up to 4 operators on a single 20A breaker. Service to header by electrician.
- Standards of Compliance:
  - UL 325 & CSA 22.2 (listed with ETL).
  - Designed to comply with these standards depending on installation and application:
    - International Building Code (Section 1008).
    - ANSI/ BHMA 156.10.
    - NFPA 101 Life Safety Code (Section 7.2.1.9).
  - Refer to Local, State, National or AHJ. Building Code for minimum door height and minimum/maximum width allowable for egress requirements.
- Contact Dorma Architectural Services for more information:
  - Email: Autosupport@dorma-usa.com
  - Phone: 1(844)773-2669