

dormakaba MUNDUS

Patch Fitting



Soaring to new heights

Designed with monumental glass doors in mind, MUNDUS combines durability, versatility and elegance

- Highest weight capacity of any patch fitting available, up to 440 lbs*
- Glass thickness range from 5/16" (8) to 7/8" (22) without changing gaskets
- Only patch fitting on the market designed specifically for use with Tempered Laminated Glass (TLG)* and Tempered Monolithic Glass
- 137" maximum door height
- Multi-directional insert adjustability - left and right as well as around the axis of rotation
- Transom patch fittings have a weight bearing capacity of 150 lb*

*Epoxy required



Design innovators

Over 25 years ago dormakaba revolutionized the glazing industry when we introduced our Dri-Fit rail to the world. With over 40 years of experience, dormakaba Interior Glass Solutions continues to be a market innovator. Leading the way with thoughtful, beautiful, and robust designs, we are often imitated, but never duplicated. dormakaba is the clear choice for making your project visibly inviting, whether you are selecting manual sliding doors for an open office environment, framed or frameless glass walls for conference rooms, or moveable glass walls that let you catch all the action in a stadium or arena. When you choose dormakaba, you choose high quality products made to last.

Unparalleled versatility

Never before has a patch fitting had flexibility like this. MUNDUS comes equipped out of the box for common glass thicknesses. The need for multiple gaskets is eliminated. Instead, two screws on the patchfitting body are used to adjust for the glass thickness, which can range from 5/16" (8) to 7/8" (22). With identical glass prep to UNIVERSAL fittings, replacing or retrofitting is a breeze.

Expanding possibilities

MUNDUS Premium fittings increase weight capacity up to 440 lb by utilizing stainless steel threads at glass attachment points, and support tempered laminated glass (TLG), offering impressive benefits such as:

- * A high level of user safety, even with large glass doors
- * Decreased noise levels enabled by integrated noise-reducing laminate
- * Glass doors as design elements utilizing decorative TLG

How does MUNDUS compare?

| | MUNDUS Premium | MUNDUS Comfort | Universal |
|------------------------|--|-------------------|--|
| Glass thickness | 1/2"–9/16" (12-15) 5/8"–3/4" (16-19) 13/16"–7/8" (20-22) | 5/16"–1/2" (8-12) | 3/8" (10) 1/2" (12) 5/8" (16) 3/4" (19) |
| Max door weight | 440 lb (200 kg) | 330 lb (150 kg) | 275 lb (125 kg) |
| Max door width* | 51-3/16" (1300) | 48" (1200) | 48" (1200) |
| Stocked in US** | Yes | Yes | Yes |

*Designed to include doors that exceed industry guidelines, confirm appropriate glass thickness for oversize doors.

** standard stocked finishes

- clear anodized
- satin stainless
- polished stainless
- custom coated finishes available upon request



Installation has never been so easy



Quick and easy to install MUNDUS fittings offer multi-dimensional in-situ adjustability, ensuring a firm and precise fit for every installation. With infinite variability of vertical gap dimensions, the pivot axis and zero position can always be correctly set.

Form and function

MUNDUS fittings impress with their elegant design, combining sharply defined straight edges and rounded corners with high-quality materials and careful workmanship. Their smooth surface finish is uninterrupted by any fixings. The cover is made of 2 mm thick stainless steel or aluminum, making it particularly robust and durable. MUNDUS is made to last, and has been tested to over 1,000,000 cycles.



Any questions? We would be happy to assist.

Contact Customer Service at 800 523 8483 or glassorders.us@dormakaba.com