



Package Width	Rough Opening Width	Clear Slide Opening	Door Panel Width	Breakout Width
(9'-6") 114" [2896]	114 1/2" [2908]	39 15/16" [1014]	29 11/16" [754]	103" [2616]
(10'-0") 120" [3048]	120 1/2" [3061]	42 15/16" [1091]	31 3/16" [792]	109" [2769]
(12'-0") 144" [3658]	144 1/2" [3670]	54 15/16" [1395]	37 3/16" [944]	133" [3378]
(14'-0") 168" [4267]	168 1/2" [4280]	66 15/16" [1700]	43 3/16" [1097]	157" [3988]
(16'-0") 192" [4877]	192 1/2" [4890]	78 15/16" [2005]	49 3/16" [1249]	181" [4597]
Width Formulas	(Package Width) + 1/2" [13]	(Package Width / 2) - 17 1/16" [433]	(Package Width / 4) + 1 3/16" [30]	(Package Width) - 11" [279]

- This Standard Bi-part door package consists of:
  - Operator:
    - Two combination motion/presence sensors (one on each side) (See sensor options page).
    - ESA II motor drive unit with self-learning and self-monitoring microprocessor controller.
    - Jamb mounted 5 function rocker switch panel (see mode switch options page).
  - Panels:
    - 4-1/2" [114] Medium stile door panels (including 3/4" [19] wide glass stop).
    - 5-1/2" [140] Optional muntin mounted at 41-3/4" [1060] centerline on all panels (including 3/4" [19] wide glass stop).
    - Recessed exit device mounted on SX panel muntins.
    - 4" [102] Bottom rails (including 3/4" [19] wide glass stop).
    - 1-3/4" [44] x 4-1/2" [114] Double pocket jambs.
    - Vertical and horizontal brush type weather stripping (AAMA-701-11Class A).
    - Manual two point mortise lock with thumb turn and key cylinder.
    - 3/4" [19] wide snap-in glass stops for glazing from 1/4" [6] to 1-1/4" [32] thick at 1/8" [3] increments.
    - ADA Compliant Surface applied track and threshold 1/2" [13] x 4 1/2" [114].
    - Breakaway sliding door panels (SX) and breakaway sidelights (SO) panels.
    - Limit arm on SX and SO Panels.
    - Breakout sensors in SO panels.
  - Finishes:
    - Clear anodized (BHMA 204).
    - Dark Bronze anodized (BHMA 313).
- Optional Transom:
  - Single vertical 1 3/4" [44] x 4 1/2" [114] double pocket mullion (Standard). Multiple verticals available.
  - Glass thickness options 1/4" [6] thru 1-1/4" [32] at 1/8" [3] increments.
  - 1/4" [6] Glass uses pocketed tubes and pressed in-glazing, top and sides.
  - Other glass thickness use snap-in sash on all sides.
- Typical Package Options:
  - Finishes: special anodized, PVDF (wet) paint, powder coat, and cladding available. header, panels and jambs only.
  - Muntins: multiple, various heights, locations and recessed exit device.
  - Bottom Rails: 7" [178], 10" [254]. Other heights available.
  - Santoprene rubber weather stripping available.
  - Locking and Security Options:
    - Bi-stable autolock sliding carrier lock concealed in header.
    - 3-point lock and reinforced strike.
    - Security contacts.
    - Keyed mode switch panel (5 function or 3 function) (see mode switch options page).
    - Recessed exit device in 5 1/2" [140] in SX muntin.
    - Surface applied 8600 exit device.
  - Recessed or 3-piece surfaced applied threshold available.
  - Jambs: 1 3/4" [44] x 4-1/2" [114].
- Drawing Notes:
  - Drawing dimensions are in English & Metric units. Metric units are displayed as: 1" [25] millimeters.
  - Typical package dimensions: (Glass thickness may be limited by panel size)
    - Each door package is manufactured to your custom size requirements.
    - Package Width: Min. 9'-6" [2896] to Max. 16' [4877].
    - Header Height: Min. 7'-4 1/2" Max. 10' [3048].
    - Package Height: Max. 12' [3658] with Transom.
    - SX Panel Weight: Max. Weight 200 lbs [90kg].
  - Maximum special application limits / custom packages: (Sizes may be restricted due to complexity and application) (Please contact dormakaba Architectural Services for dimensions **outside of typical sizes above**)
    - Package Width: Min. 8'-6" [2591] to Max. 18' [5486].
    - Package Height: Max. 14' [4267].
    - Header Height: Max. 12' [3658].
    - Transom Height: Min. 8" [203] to Max. 2' [610].
    - SX Panel Width: Max. Width 56" [1422].
    - SO Panel Width: Max. Width 60" [1524].
    - SO Panel Weight: Max. 250 lbs [113 kg].
    - SX Panel Size Limit = (SX Panel Width x Weight) < 800 ft-lbs [1084 N-m] Max.
- Power Requirements:
  - 120V +/- 10%, 50/60 Hz, 6.6A peak, 250 W. Up to 4 operators on a single 20A breaker. Service to header by electrician.
- Standards of Compliance:
  - UL 325 & CSA 22.2 (listed with ETL).
  - Designed to comply with these standards depending on installation and application:
    - International Building Code (Section 1008).
    - ANSI/ BHMA 156.10.
    - ANSI/ BHMA 156.38.
    - NFPA 101 Life Safety Code (Section 7.2.1.9).
  - Refer to Local, State, National or AHJ. Building Code for minimum door height and minimum/maximum width allowable for egress requirements.
  - Minimum ADA is 32" clear slide opening.