

125kHz Proximity Cards & Fobs



Frequency & Range
125kHz, Up To 6-1/2" (165mm)



Interface
26-Bit, Wiegand
HID® & AWID®
Supported

Passive proximity cards and fobs
for physical access control



125kHz Proximity Cards & Fobs



Using proven contactless digital radio frequency identification (RFID) technology, RCI cards and fobs set the electronic security benchmark for 125kHz proximity products.



	1326R Clamshell Card	1386R Printable Card	1314R Thick Printable Card	1346R Proximity Fob
Technology	Proximity			
Frequency	125kHz			
Operation	Passive (no battery)			
Format	26-bit			
Material	ABS	PVC	PVC	ABS
Color	Off-white	Glossy white	Glossy white	Gray
Marking ¹	Date code and ID			
Read Range ²	Up to 5-1/2" (140mm)	Up to 5" (127mm)	Up to 6-1/2" (165mm)	Up to 4-1/2" (114mm)
Warranty	Limited lifetime warranty	1 Year	Limited lifetime warranty	Limited lifetime warranty
Dimensions	2-3/16"W x 3-3/8"H x 1/16"D (56mm x 86mm x 1.5mm)	2-1/16"W x 3-3/8"H x 1/32"D (53mm x 86mm x 0.79mm)	2-1/16"W x 3-3/8"H x 1/16"D (53mm x 86mm x 1.17mm)	1-1/2"W x 1-3/16"H x 1/8"D (38mm x 30mm x 3.8mm)
Weight	0.3oz (9g)	0.19oz (5.5g)	0.3oz (9g)	0.16oz (4.5g)
Operating Temperature	-35°F to 122°F (-37°C to +50°C)			
Humidity	0-95% non-condensing			
Protocols	Item code suffix: R – Standard RCI proximity protocol R-H – Certain HID® proximity protocols R-A – Certain AWID® proximity protocols			
Packaging	Sold in packs of 10, 25 and 50			
Options ³	Custom facility codes, formats, printing and slot punching available			
Imaging ⁴	Glossy adhesive overlay for color dye sublimation printing or print directly on card	Supports dye sublimation imaging	Supports dye sublimation imaging	N/A
Slot Punch	Standard, vertical	Vertical & horizontal indicators	Vertical & horizontal indicators	Standard, reinforced brass eyelet

1. Matching internal and external sequential coding standard. Custom printing available.
2. Tested with 12VDC @ 5395R reader.
3. Contact RCI to learn how you can customize your cards and fobs.
4. Please verify that the printer (or overlay) supports credential type/thickness.

AWID is a trademark of Applied Wireless Identifications Group. HID is a registered trademarks of HID Global Corporation, an ASSA ABLOY company. All other trademarks are the property of their respective owners. RCI reserves the right to change specifications without notice.