

HSW-ES

Horizontal sliding glass walls



Our new horizontal sliding wall solution features redesigned rails for fast and easy installation. The HSW-ES system allows unlimited interior design options to make planning and specification far less complicated.

Achieve a high level of creativity and flexibility with the optional use of tempered laminated glass to transform open spaces both visually and audibly.

The HSW-ES wall system offers clear advantages affording transparency, acoustics, and safety.

Conveniently bolted to floor using simple foot-activated floor bolting devices.

- Component standardization simplifies planning and significantly reduces installation time—regardless of the opening.
- Double brush seals in top and bottom rails and an optional bulb gasket assure proper sealing to control air circulation.

Locking status at a glance

The top locking device displays the status of the door panel with visual indicators.

Trouble-free installation

The modular design of the HSW-ES system allows sliding and pivoting panels to be arranged in countless ways. Discover total design flexibility and diversity, including perpendicular or parallel panel parking. The optional ITS concealed in-door closer provides door control for convertible panels.

Finish options

Choose from aluminum, satin stainless, or more than 200 custom RAL colors.

Our exclusive clamp & glue technology™ will change the way you see tempered laminated glass installation.




dormakaba's proprietary Clamp & Glue Technology™ is a tested and proven solution for assembling safe and secure interior tempered laminated glass walls.

The unmatched clamping power is achieved by a specialized application of the adhesive through precision-engineered clamps to form an incredibly strong and stable bond. Tempered laminated glass panels are ready for installation in as little as 20 minutes.


Specifications

Max height	10' (3048)
Max panel width	49" (1245)
Max panel weight	330 lb (150 kg)
Glass thickness	3/8" to 3/4" (10-19)
Convertible sliding and fixed end panels	Single or double acting
Standard finishes	628 satin aluminum 630 satin stainless

Note: Width measurements are shown as inches followed by millimeters; for example, 1" (25).

Status display			
Sliding function	Locked	Locked	Open
Door function	Open	Locked	Locked

Convenient opening and closing



Door panel bolts are easily operated by simple activation with your foot.

© dormakaba 2024 Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation.

Any questions? We would be happy to advise you.
Contact us at: 1-800-265-6630