## dormakaba 🚧

# InSync<sup>®</sup> L Series Electronic Lock



### Overview

The InSync L is a battery operated electronic lock with a tubular dead-locking latch bolt. An InSync L lock works with Windows®-based SAM RF software, an electronic key-encoding device, handheld utility device, and electronic RFID keys to create a comprehensive access control system. The system eliminates key cutting, lock replacement, and risks associated with unauthorized mechanical keys. In addition, it provides multiple levels of access control to provide the highest level of security.

#### Applications


- Ideal for all types of multihousing applications, including apartment homes, student housing, assisted-living facilities, and military family housing
- Suitable for both new and retrofit projects
- Access control for unit, suite, and common areas

#### Security Features

- Dead-latching bolt operates with closure of the door
- Inhibit key cancels a specific key; for use when a key is lost or stolen
- Emergency keys open any lock on a property, including unit, suite, and common access area locks
- Limited Use keys for vendors, staff members, and potential residents who may need regulated access to unit or common access areas

#### Low Maintenance

- Locks indicate low power signal with key insertion
- Designed for extended battery life
- Weatherized to withstand environmental conditions



The InSync "L" unit lock provides true residential entry lock functionality. Each time the inside lever is rotated the lock enters an unlocked state, eliminating the possibility of a lockout. Insertion of the key and rotation of the outside lever provides ingress and always returns the lock into the unlocked position. Inserting the key into the lock after egress, places the lock back into the locked position. The inside thumbturn toggles the lock from unlocked to locked. With the Entry Configuration, the InSync "L" unit lock behaves like a hotel lock; the lock will always re-lock behind a resident and the thumbturn works like a privacy switch.

Suite locks allow access to residents who have individual units behind the suite door. Suite locks automatically re-lock and do not have a privacy feature (thumbturn); however with the Suite Egress Configuration, a Suite lock acts like a Unit lock where the key or thumbturn is used to manually re-lock the lock.

Unit or Suite locks can recognize up to 256 individual key IDs plus unlimited "Limited Use Key" IDs at any time. Common locks provide access to common use areas, such as fitness center, parking garage, and pool.

#### Features

| Credential             | Locks use an RFID memory key that employs special polymer construction to repel moisture. The InSync RFID key with dual technologies includes standard HiTag technology along with Prox, MIFARE® or DESFire® option. |
|------------------------|--|
| Locking device options | Tubular dead-locking latch bolt  |
| Audit trail            | Unit locks store the last 200 entries to the lock and Suite locks store the last 100 entries, including time, day, and key identification or user name. Common locks can store up to 2,000 entries.                  |
| Programming            | Locks and common readers are programmed and audited using a Utility Device<br>Key levels Resident, zone, master, limited use, and emergency  |
| Mechanical Features    |  |
| Exterior dimensions    | 8 ¾" h x 3 ⅛" w x 2 ¼" d   |
| Latch                  | ½" tubular deadlatch   |
| Power                  | Four (4) standard size AA alkaline batteries   |
| Levers                 | ADA compliant<br>Arc Continental Gala Troy Vintage Apogee<br>Note: Verify that Vintage, Gala, and Arc levers comply with local fire code requirements.   |
| Backset                | 2 ¾" (60mm) or 2 ¾" (70mm), non-adjustable — no special tools required   |
| Weight                 | 8lbs (3.62 kg)   |
| Installation           |  |
| Door preparation       | Standard deadbolt  |
| Door thickness         | 1 3/8" - 2" (35mm to 51mm)   |
| Fire rating            | UL certified for use on fire-rated doors up to a 20 minute rating  |
| Environmental          | Indoor/outdoor approval: -31° F to 151° F (-35° C to 66° C)  |
| Accessibility standard | ADA compliant levers and thumb turn  |
| Warranty               |  |
| Standard warranty      | One year from date of installation   |
| Extended warranty      | dormakaba Service Plans (Platinum, Gold, Silver) (formerly Kaba service plans)   |
| Standard finishes      | Bright chrome (26) Satin chrome (26D) Bright brass (U3) Satin Brass (U4)   |
| Optional finishes      | Satin Nickel (U15) Dark Mahogany (10B)   |

© dormakaba 2019 Information on this sheet is intended for general use only. dormakaba reserves the right to alter designs and specifications without notice or obligation.

dormakaba USA Inc. 2941 Indiana Ave. Winston-Salem NC 27105 T: 1 800 849 8324